



1. The drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. Rough Opening Width and Height should typically be 1/2" greater than the Unit/Frame Dimension.
3. Glass Sizes and additional dimensions are available on the Dimensions page at the back of this section.
4. Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
5. The standard jamb depth is 4-9/16". Frame Extension may be added to increase the jamb depth to 6-9/16".
6. Unit Sizes have a tolerance of + / - .0625" per frame/unit dimensions

1-Panel Units


		Fixed Only					
Unit/Frame H.	R.O. Height	Panel Height				Unit/Frame Width	
						R.O. Width	
						Panel Width	
79 15/16"	80 1/2"	77 1/16"	25 1/4"	31 1/4"	33 1/4"	37 1/4"	40 1/4"
82 15/16"	83 1/2"	80 1/16"	25 3/4"	31 3/4"	33 3/4"	37 3/4"	40 3/4"
95 15/16"	96 1/2"	93 1/16"	22 11/16"	28 11/16"	30 11/16"	34 11/16"	37 11/16"

2-Panel Units

		Fixed Only							
Unit/Frame H.	R.O. Height	Panel Height						Unit/Frame Width	
								R.O. Width	
								Panel Width ea.	
79 15/16"	80 1/2"	77 1/16"	48 7/8"	60 7/8"	64 7/8"	72 7/8"	90 1/2"	96 1/2"	108 1/2"
82 15/16"	83 1/2"	80 1/16"	49 3/8"	61 3/8"	65 3/8"	73 3/8"	91"	97"	109"
95 15/16"	96 1/2"	93 1/16"	22 11/16"	28 11/16"	30 11/16"	34 11/16"	28 11/16"	30 11/16"	34 11/16"

3-Panel Units

Operation Options for In-Swing Doors - Specify the operation for the door as shown below. Operation is as viewed from the outside.





True French In-Swing Door Sizes

1. The drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. Rough Opening Width and Height should typically be 1/2" greater than the Unit/Frame Dimension.
3. Glass Sizes and additional dimensions are available on the Dimensions page at the back of this section.
4. Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
5. The standard jamb depth is 4-9/16". Frame Extension may be added to increase the jamb depth to 6-9/16".
6. Unit Sizes have a tolerance of + / - .0625" per frame/unit dimensions

Unit/Frame H.	Unit/Frame Width	R.O. Height	R.O. Width	Panel Width ea.
48 7/8"	60 7/8"	64 7/8"	72 7/8"	Unit/Frame Width
49 3/8"	61 3/8"	65 3/8"	73 3/8"	R.O. Width
22 11/16"	28 11/16"	30 11/16"	34 11/16"	Panel Width ea.
79 15/16"		80 1/2"		
82 15/16"		83 1/2"		
95 15/16"		96 1/2"		

Operation Options for True French Doors - Specify the operation for the door as shown below. Operation is as viewed from the outside.

