



Bay Windows

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = see chart.
- Unit / Frame Height = Call Height + 4" + 2 1/2" for Head & Seat Board (1 1/4" x 2). Specified in inches.
- Rough Opening Width = Unit/Frame Width + 3/8". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Projection is measured from the exterior mounting surface (exterior sheathing) to the outer-most edge of the bay window.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.

Call Height Unit/Frame Ht R.O. Height	12/44/12	16/44/16	20/44/20	12/52/12	16/52/16	12/60/12	Call Width	
		79 7/16"	86 7/16"	93 5/16"	87 7/16"	94 7/16"	95 7/16"	Unit/Frame Width
	6'-7 13/16"	7'-2 11/16"	7'-9 11/16"	7'-3 13/16"	7'-10 13/16"	7'-11 13/16"	R.O. Width	
	10 11/16"	12 11/16"	14 11/16"	10 11/16"	12 11/16"	10 11/16"	Projection	
	30°							
44 50 1/2" 4'-3"								
	CCB30/124412/44	CCB30/164416/44	CCB30/204420/44	CCB30/125212/44	CCB30/165216/44	CCB30/126012/44		
55 61 1/2" 5'-2"								
	CCB30/124412/55	CCB30/164416/55	CCB30/204420/55	CCB30/125212/55	CCB30/165216/55	CCB30/126012-55		
68 74 1/2" 6'-3"								
	CCB30/124412/68	CCB30/164416/68	CCB30/204420/68	CCB30/125212/68	CCB30/165216/68	CCB30/126012-68		
	12/44/12	16/44/16	20/44/20	12/52/12	16/52/16	12/60/12	Call Width	
	76 1/8"	81 3/4"	87 3/8"	84 1/8"	89 3/4"	92 1/8"	Unit/Frame Width	
	6'-4 1/2"	6'-10 1/8"	7'-3 3/4"	7'-0 1/2"	7'-6 1/8"	7'-8 1/2"	R.O. Width	
	14 15/16"	17 3/4"	20 5/8"	14 15/16"	17 3/4"	14 15/16"	Projection	
	45°							
44 50 1/2" 4'-3"								
	CCB45/124412/44	CCB45/164416/44	CCB45/204420/44	CCB45/125212/44	CCB45/165216/44	CCB45/126012/44		
55 61 1/2" 5'-2"								
	CCB45/124412/55	CCB45/164416/55	CCB45/204420/55	CCB45/125212/55	CCB45/165216/55	CCB45/126012/55		
68 74 1/2" 6'-3"								
	CCB45/124412/68	CCB45/164416/68	CCB45/204420/68	CCB45/125212/68	CCB45/165216/68	CCB45/126012/68		
	12-4	16-4	20-4	12-4	16-4	20-4	Call Width	
	63 7/16"	78 7/16"	93 5/16"	60 1/8"	73 3/4"	87 3/8"	Unit/Frame Width	
	5'-3 13/16"	6'-6 13/16"	7'-9 11/16"	5'-0 1/2"	6'-2 1/8"	7'-3 3/4"	R.O. Width	
	10 11/16"	12 11/16"	14 11/16"	14 15/16"	17 3/4"	20 5/8"	Projection	
	30°		30°		45°			
44 50 1/2" 4'-3"								
	CCB30/12-4/44	CCB30/16-4/44	CCB30/20-4/44	CCB45/12-4/44	CCB45/16-4/44	CCB45/20-4/44		
55 61 1/2" 5'-2"								
	CCB30/12-4/55	CCB30/16-4/55	CCB30/20-4/55	CCB45/12-4/55	CCB45/16-4/55	CCB45/20-4/55		
68 74 1/2" 6'-3"								
	CCB30/12-4/68	CCB30/16-4/68	CCB30/20-4/68	CCB45/12-4/68	CCB45/16-4/68	CCB45/20-4/68		



Bow Windows

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = see chart.
4. Unit / Frame Height = Call Height + 4" + 2 1/2" for Head & Seat Board (1 1/4" x 2). Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 3/8". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
7. Projection is measured from the exterior mounting surface (exterior sheathing) to the outer-most edge of the bay window.
8. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
9. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.

Call Height Unit/Frame Ht R.O. Height	12-4	16-4	20-4	Call Width
	64 7/8"	80 9/16"	96 5/16"	Unit/Frame Width
	5'-5 1/4"	6'-8 15/16"	8'-0 11/16"	R.O. Width
	7 9/16"	8 15/16"	10 3/8"	Projection
44 50 1/2" 4'-3"	1	4	7	
	CCB10/12-4/44	CCB10/16-4/44	CCB10/20-4/44	
55 61 1/2" 5'-2"	2	5	8	
	CCB10/12-4/55	CCB10/16-4/55	CCB10/20-4/55	
68 74 1/2" 6'-3"	3	6	9	
	CCB10/12-4/68	CCB10/16-4/68	CCB10/20-4/68	
	12-5	16-5		Call Width
	80 1/4"	99 5/8"		Unit/Frame Width
	6'-8 5/8"	8'-4"		R.O. Width
	10 7/16"	12 1/2"		Projection
44 50 1/2" 4'-3"	10	13		
	CCB10/12-5/44	CCB10/16-5/44		
55 61 1/2" 5'-2"	11	14		
	CCB10/12-5/55	CCB10/16-5/55		
68 74 1/2" 6'-3"	12	15		
	CCB10/12-5/68	CCB10/16-5/68		
	12-6			Call Width
	95"			Unit/Frame Width
	7'-11 3/8"			R.O. Width
	14 3/4"			Projection
44 50 1/2" 4'-3"	16			
	CCB10/12-6/44			
55 61 1/2" 5'-2"	17			
	CCB10/12-6/55			
68 74 1/2" 6'-3"	18			
	CCB10/12-6/68			