



# Comfort-Tilt Double Hung Sizes: 1-wide


- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = (Call Height x 2) + 6-3/16". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 9/16". Specified in feet and inches.
- Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
- Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH	Call Height - FX	Unit/Frame Height	R.O. Height	16	20	24	28	32	36	40	Call Width
				20"	24"	28"	32"	36"	40"	44"	Unit/Frame Width
				1'-8 1/2"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	3'-8 1/2"	R.O. Width
14	30 3/16"	34 3/16"	2'-10 3/4"	1	9	17	25	33	41	49	
	30 3/16"	34 3/16"	2'-10 3/4"	CDHZ1614	CDHZ2014	CDHZ2414	CDHZ2814	CDHZ3214	CDHZ3614	CDHZ4014	
16	34 3/16"	38 3/16"	3'-2 3/4"	2	10	18	26	34	42	50	
	34 3/16"	38 3/16"	3'-2 3/4"	CDHZ1616	CDHZ2016	CDHZ2416	CDHZ2816	CDHZ3216	CDHZ3616	CDHZ4016	
20	42 3/16"	46 3/16"	3'-10 3/4"	3	11	19	27	35	43	51	
	42 3/16"	46 3/16"	3'-10 3/4"	CDHZ1620	CDHZ2020	CDHZ2420	CDHZ2820	CDHZ3220	CDHZ3620	CDHZ4020	
22	46 3/16"	50 3/16"	4'-2 3/4"	4	12	20	28	36	44	52	
	46 3/16"	50 3/16"	4'-2 3/4"	CDHZ1622	CDHZ2022	CDHZ2422	CDHZ2822	CDHZ3222	CDHZ3622	CDHZ4022	
24	50 3/16"	54 3/16"	4'-6 3/4"	5	13	21	29	37	45	53	
	50 3/16"	54 3/16"	4'-6 3/4"	CDHZ1624	CDHZ2024	CDHZ2424	CDHZ2824	CDHZ3224	CDHZ3624	CDHZ4024	
28	58 3/16"	62 3/16"	5'-2 3/4"	6	14	22	30	38	46	54	
	58 3/16"	62 3/16"	5'-2 3/4"	CDHZ1628	CDHZ2028	CDHZ2428	CDHZ2828	CDHZ3228	CDHZ3628	CDHZ4028	
32	66 3/16"	70 3/16"	5'-10 3/4"	7	15	23	31	39	47	55	
	66 3/16"	70 3/16"	5'-10 3/4"	CDHZ1632	CDHZ2032	CDHZ2432	CDHZ2832	CDHZ3232	CDHZ3632	CDHZ4032	
34	70 3/16"	74 3/16"	6'-2 3/4"	8	16	24	32	40	48	56	
	70 3/16"	74 3/16"	6'-2 3/4"	CDHZ1634	CDHZ2034	CDHZ2434	CDHZ2834	CDHZ3234	CDHZ3634	CDHZ4034	

### Grille Patterns



No Grille



Colonial



Lexington



# Comfort-Tilt Double Hung Sizes: 2-wide

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = (Call Height x 2) + 6-3/16". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 9/16". Specified in feet and inches.
- Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
- Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH Call Height - FX Unit/Frame Height R.O. Height	16-2	20-2	24-2	28-2	32-2	36-2	40-2	Call Width
	40"	48"	56"	64"	72"	80"	88"	Unit/Frame Width
	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	6'-8 1/2"	7'-4 1/2"	R.O. Width
14	57 CDHZ1614-2	65 CDHZ2014-2	73 CDHZ2414-2	81 CDHZ2814-2	89 CDHZ3214-2	97 CDHZ3614-2	105 CDHZ4014-2	<b>Grille Patterns</b>  No Grille  Colonial  Lexington
16	58 CDHZ1616-2	66 CDHZ2016-2	74 CDHZ2416-2	82 CDHZ2816-2	90 CDHZ3216-2	98 CDHZ3616-2	106 CDHZ4016-2	
20	59 CDHZ1620-2	67 CDHZ2020-2	75 CDHZ2420-2	83 CDHZ2820-2	91 CDHZ3220-2	99 CDHZ3620-2	107 CDHZ4020-2	
22	60 CDHZ1622-2	68 CDHZ2022-2	76 CDHZ2422-2	84 CDHZ2822-2	92 CDHZ3222-2	100 CDHZ3622-2	108 CDHZ4022-2	
24	61 CDHZ1624-2	69 CDHZ2024-2	77 CDHZ2424-2	85 CDHZ2824-2	93 CDHZ3224-2	101 CDHZ3624-2	109 CDHZ4024-2	
28	62 CDHZ1628-2	70 CDHZ2028-2	78 CDHZ2428-2	86 CDHZ2828-2	94 CDHZ3228-2	102 CDHZ3628-2	110 CDHZ4028-2	
32	63 CDHZ1632-2	71 CDHZ2032-2	79 CDHZ2432-2	87 CDHZ2832-2	95 CDHZ3232-2	103 CDHZ3632-2	111 CDHZ4032-2	
34	64 CDHZ1634-2	72 CDHZ2034-2	80 CDHZ2434-2	88 CDHZ2834-2	96 CDHZ3234-2	104 CDHZ3634-2	112 CDHZ4034-2	



# Comfort-Tilt Double Hung Sizes: 3-wide

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
4. Unit / Frame Height = (Call Height x 2) + 6-3/16". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 5/8". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 9/16". Specified in feet and inches.
7. Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
8. Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
9. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
10. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
11. Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
12. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
13. Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
14. Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH	Call Height - FX	Unit/Frame Height	R.O. Height	16-3	20-3	24-3	28-3	32-3	36-3	40-3	Call Width
				60"	72"	84"	96"	108"	120"	132"	Unit/Frame Width
				5'-0 5/8"	6'-0 5/8"	7'-0 5/8"	8'-0 5/8"	9'-0 5/8"	10'-0 5/8"	11'-0 5/8"	R.O. Width
14	30 3/16"	34 3/16"	2'-10 3/4"	113	121	129	137	145	153	161	
	30 3/16"	34 3/16"	2'-10 3/4"								
16	34 3/16"	38 3/16"	3'-2 3/4"	114	122	130	138	146	154	162	
	34 3/16"	38 3/16"	3'-2 3/4"								
20	42 3/16"	46 3/16"	3'-10 3/4"	115	123	131	139	147	155	163	
	42 3/16"	46 3/16"	3'-10 3/4"								
22	46 3/16"	50 3/16"	4'-2 3/4"	116	124	132	140	148	156	164	
	46 3/16"	50 3/16"	4'-2 3/4"								
24	50 3/16"	54 3/16"	4'-6 3/4"	117	125	133	141	149	157	165	
	50 3/16"	54 3/16"	4'-6 3/4"								
28	58 3/16"	62 3/16"	5'-2 3/4"	118	126	134	142	150	158	166	
	58 3/16"	62 3/16"	5'-2 3/4"								
32	66 3/16"	70 3/16"	5'-10 3/4"	119	127	135	143	151	159	167	
	66 3/16"	70 3/16"	5'-10 3/4"								
34	70 3/16"	74 3/16"	6'-2 3/4"	120	128	136	144	152	160	168	
	70 3/16"	74 3/16"	6'-2 3/4"								

### Grille Patterns



No Grille

Colonial

Lexington