



# Bay Windows

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = see chart.
4. Unit / Frame Height = Fixed Lite Call Height + 4" + 2 1/2" for Head & Seat Board (1 1/4" x 2). Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 3/8". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
7. Projection is measured from the exterior mounting surface (exterior sheathing) to the outer-most edge of the bay window.
8. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
9. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.

Call Height - DH Call Height - FX Unit/Frame Ht R.O. Height	30°					Call Width
	16-3	20-3	24-3	16-4	20-4	Unit/Frame Width
24 50 3/16"	58 7/16"	69 5/16"	80 5/16"	78 7/16"	93 5/16"	Unit/Frame Width
50 3/16"	4'-10 13/16"	5'-9 11/16"	6'-8 11/16"	6'-6 13/16"	7'-9 11/16"	R.O. Width
56 11/16"	12 11/16"	14 11/16"	16 11/16"	12 11/16"	14 11/16"	Projection
28 58 3/16"						
58 3/16"	CDZB30/16-3/24	CDZB30/20-3/24	CDZB30/24-3/24	CDZB30/16-4/24	CDZB30/20-4/24	
64 11/16"						
64 11/16"	CDZB30/16-3/28	CDZB30/20-3/28	CDZB30/24-3/28	CDZB30/16-4/28	CDZB30/20-4/28	
5'-5 3/16"						
66 3/16"	CDZB30/16-3/32	CDZB30/20-3/32	CDZB30/24-3/32	CDZB30/16-4/32	CDZB30/20-4/32	
72 11/16"	<b>16-3</b>	<b>20-3</b>	<b>24-3</b>	<b>16-4</b>	<b>20-4</b>	Call Width
6'-1 3/16"	53 3/4"	63 3/8"	73 1/8"	73 3/4"	87 3/8"	Unit/Frame Width
	4'-6 1/8"	5'-3 3/4"	6'-1 1/2"	6'-2 1/8"	7'-3 3/4"	R.O. Width
	17 3/4"	20 5/8"	23 7/16"	17 3/4"	20 5/8"	Projection
24 50 3/16"						
50 3/16"	CDZB45/16-3/24	CDZB45/20-3/24	CDZB45/24-3/24	CDZB45/16-4/24	CDZB45/20-4/24	
56 11/16"						
56 11/16"	CDZB45/16-3/28	CDZB45/20-3/28	CDZB45/24-3/28	CDZB45/16-4/28	CDZB45/20-4/28	
5'-5 3/16"						
66 3/16"	CDZB45/16-3/32	CDZB45/20-3/32	CDZB45/24-3/32	CDZB45/16-4/32	CDZB45/20-4/32	
72 11/16"	<b>16/44/16</b>	<b>20/44/20</b>	<b>16/52/16</b>	<b>16/44/16</b>	<b>20/44/20</b>	Call Width
6'-1 3/16"	86 7/16"	93 5/16"	94 7/16"	81 3/4"	87 3/8"	Unit/Frame Width
	7'-2 13/16"	7'-9 11/16"	7'-10 13/16"	6'-10 1/8"	7'-3 3/4"	R.O. Width
	12 11/16"	14 11/16"	12 11/16"	17 3/4"	20 5/8"	Projection
24 50 3/16"						
50 3/16"	CDZB30/164416/24	CDZB30/204420/24	CDZB30/165216/24	CDZB45/164416/24	CDZB45/204420/24	CDZB45/165216/24
56 11/16"						
56 11/16"	CDZB30/164416/28	CDZB30/204420/28	CDZB30/165216/28	CDZB45/164416/28	CDZB45/204420/28	CDZB45/165216/28
5'-5 3/16"						
66 3/16"	CDZB30/164416/32	CDZB30/204420/32	CDZB30/165216/32	CDZB45/164416/32	CDZB45/204420/32	CDZB45/165216/32