



Easy-Tilt Double Hung Sizes: 1-wide


- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = (Call Height x 2) + 6-3/16". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 9/16". Specified in feet and inches.
- Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
- Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH	Call Width						
	16	20	24	28	32	36	40
14	20"	24"	28"	32"	36"	40"	44"
16	20"	24"	28"	32"	36"	40"	44"
20	20"	24"	28"	32"	36"	40"	44"
22	20"	24"	28"	32"	36"	40"	44"
24	20"	24"	28"	32"	36"	40"	44"
28	20"	24"	28"	32"	36"	40"	44"
32	20"	24"	28"	32"	36"	40"	44"
34	20"	24"	28"	32"	36"	40"	44"
	1'-8 1/2"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	3'-8 1/2"
							R.O. Width
	CDZ1614	CDZ2014	CDZ2414	CDZ2814	CDZ3214	CDZ3614	CDZ4014
	CDZ1616	CDZ2016	CDZ2416	CDZ2816	CDZ3216	CDZ3616	CDZ4016
	CDZ1620	CDZ2020	CDZ2420	CDZ2820	CDZ3220	CDZ3620	CDZ4020
	CDZ1622	CDZ2022	CDZ2422	CDZ2822	CDZ3222	CDZ3622	CDZ4022
	CDZ1624	CDZ2024	CDZ2424	CDZ2824	CDZ3224	CDZ3624	CDZ4024
	CDZ1628	CDZ2028	CDZ2428	CDZ2828	CDZ3228	CDZ3628	CDZ4028
	CDZ1632	CDZ2032	CDZ2432	CDZ2832	CDZ3232	CDZ3632	CDZ4032
	CDZ1634	CDZ2034	CDZ2434	CDZ2834	CDZ3234	CDZ3634	CDZ4034

Grille Patterns



No Grille



Colonial



Lexington



Easy-Tilt Double Hung Sizes: 2-wide

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
4. Unit / Frame Height = (Call Height x 2) + 6-3/16". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 9/16". Specified in feet and inches.
7. Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
8. Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
9. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
10. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
11. Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
12. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
13. Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
14. Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH Call Height - FX Unit/Frame Height R.O. Height	16-2	20-2	24-2	28-2	32-2	36-2	40-2	Call Width
	40"	48"	56"	64"	72"	80"	88"	Unit/Frame Width
	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	6'-8 1/2"	7'-4 1/2"	R.O. Width
14 30 3/16" 34 3/16" 2'-10 3/4"	57 CDZ1614-2	65 CDZ2014-2	73 CDZ2414-2	81 CDZ2814-2	89 CDZ3214-2	97 CDZ3614-2	105 CDZ4014-2	Grille Patterns No Grille Colonial Lexington
16 34 3/16" 38 3/16" 3'-2 3/4"	58 CDZ1616-2	66 CDZ2016-2	74 CDZ2416-2	82 CDZ2816-2	90 CDZ3216-2	98 CDZ3616-2	106 CDZ4016-2	
20 42 3/16" 46 3/16" 3'-10 3/4"	59 CDZ1620-2	67 CDZ2020-2	75 CDZ2420-2	83 CDZ2820-2	91 CDZ3220-2	99 CDZ3620-2	107 CDZ4020-2	
22 46 3/16" 50 3/16" 4'-2 3/4"	60 CDZ1622-2	68 CDZ2022-2	76 CDZ2422-2	84 CDZ2822-2	92 CDZ3222-2	100 CDZ3622-2	108 CDZ4022-2	
24 50 3/16" 54 3/16" 4'-6 3/4"	61 CDZ1624-2	69 CDZ2024-2	77 CDZ2424-2	85 CDZ2824-2	93 CDZ3224-2	101 CDZ3624-2	109 CDZ4024-2	
28 58 3/16" 62 3/16" 5'-2 3/4"	62 CDZ1628-2	70 CDZ2028-2	78 CDZ2428-2	86 CDZ2828-2	94 CDZ3228-2	102 CDZ3628-2	110 CDZ4028-2	
32 66 3/16" 70 3/16" 5'-10 3/4"	63 CDZ1632-2	71 CDZ2032-2	79 CDZ2432-2	87 CDZ2832-2	95 CDZ3232-2	103 CDZ3632-2	111 CDZ4032-2	
34 70 3/16" 74 3/16" 6'-2 3/4"	64 CDZ1634-2	72 CDZ2034-2	80 CDZ2434-2	88 CDZ2834-2	96 CDZ3234-2	104 CDZ3634-2	112 CDZ4034-2	



Easy-Tilt Double Hung Sizes: 3-wide

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
4. Unit / Frame Height = (Call Height x 2) + 6-3/16". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 5/8". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 9/16". Specified in feet and inches.
7. Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
8. Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
9. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
10. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
11. Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
12. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
13. Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
14. Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH	16-3	20-3	24-3	28-3	32-3	36-3	40-3	Call Width
30 3/16"	60"	72"	84"	96"	108"	120"	132"	Unit/Frame Width
34 3/16"	5'-0 5/8"	6'-0 5/8"	7'-0 5/8"	8'-0 5/8"	9'-0 5/8"	10'-0 5/8"	11'-0 5/8"	R.O. Width
34 3/16"	113	121	129	137	145	153	161	
38 3/16"	CDZ1614-3	CDZ2014-3	CDZ2414-3	CDZ2814-3	CDZ3214-3	CDZ3614-3	CDZ4014-3	
38 3/16"	114	122	130	138	146	154	162	
42 3/16"	CDZ1616-3	CDZ2016-3	CDZ2416-3	CDZ2816-3	CDZ3216-3	CDZ3616-3	CDZ4016-3	
46 3/16"	115	123	131	139	147	155	163	
50 3/16"	CDZ1620-3	CDZ2020-3	CDZ2420-3	CDZ2820-3	CDZ3220-3	CDZ3620-3	CDZ4020-3	
54 3/16"	116	124	132	140	148	156	164	
58 3/16"	CDZ1622-3	CDZ2022-3	CDZ2422-3	CDZ2822-3	CDZ3222-3	CDZ3622-3	CDZ4022-3	
62 3/16"	117	125	133	141	149	157	165	
66 3/16"	CDZ1624-3	CDZ2024-3	CDZ2424-3	CDZ2824-3	CDZ3224-3	CDZ3624-3	CDZ4024-3	
70 3/16"	118	126	134	142	150	158	166	
74 3/16"	CDZ1628-3	CDZ2028-3	CDZ2428-3	CDZ2828-3	CDZ3228-3	CDZ3628-3	CDZ4028-3	
74 3/16"	119	127	135	143	151	159	167	
78 3/16"	CDZ1632-3	CDZ2032-3	CDZ2432-3	CDZ2832-3	CDZ3232-3	CDZ3632-3	CDZ4032-3	
78 3/16"	120	128	136	144	152	160	168	
82 3/16"	CDZ1634-3	CDZ2034-3	CDZ2434-3	CDZ2834-3	CDZ3234-3	CDZ3634-3	CDZ4034-3	

Grille Patterns



No Grille



Colonial



Lexington