











- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4". Specified in inches.
- Unit / Frame Height = Shoulder Height + Cord Height. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Shoulder Height is the height of the straight vertical portion of the unit. Match the shoulder height to the unit height of other non-radius products for side mulling.
- Cord Height is the height of the curved top portion of the window.
- The Radius is the arc of the curved portion of the window.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.





| Call Height - DH Call Height - FX Shoulder Height | Eyebrow Window | | | | | | | | Call W. | |
|---|--|-----------|-----------|-----------|-----------|------------|-----------|-----------|-----------|-----------|
| | | 20 | 24 | 28 | 32 | 36 | 44 | 52 | 60 | 68 |
| | 24" | 28" | 32" | 36" | 40" | 48" | 56" | 64" | 72" | Unit W. |
| | 2'-0 1/2" | 2'-4 1/2" | 2'-8 1/2" | 3'-0 1/2" | 3'-4 1/2" | 4'-0 1/2" | 4'-8 1/2" | 5'-4 1/2" | 6'-0 1/2" | R.O. W. |
| | | | | | | 28" | 32" | 36" | 42" | Radius |
| | | | | | | 13 9/16" | 16 1/2" | 19 1/2" | 20 3/8" | Cord H. |
| 0" |  | | | | | | | | | |
| | Colonial Grille Pattern | | | | | | | | | |
| |  | | | | | | | | | |
| | Spoke Grille Pattern | | | | | | | | | |
| | | | | | | CCE44 | CCE52 | CCE60 | CCE68 | Call Size |
| | | | | | | 48" | 56" | 64" | 72" | Unit W. |
| | | | | | | 13 9/16" | 16 1/2" | 19 1/2" | 20 3/8" | Unit H. |
| | | | | | | 4'-0 1/2" | 4'-8 1/2" | 5'-4 1/2" | 6'-0 1/2" | R.O. W. |
| | | | | | | 1'-2 1/16" | 1'-5" | 1'-8" | 1'-8 7/8" | R.O.H. |

| Call Height - DH Call Height - FX Shoulder Height | Gothic Window | | | | | | | | Call W. | |
|---|---|--------------|-------------|------------|-----------|-----------|-----------|-----------|-----------|-----------|
| | | 20 | 24 | 28 | 32 | 36 | 44 | 52 | 60 | 68 |
| | 24" | 28" | 32" | 36" | 40" | 48" | 56" | 64" | 72" | Unit W. |
| | 2'-0 1/2" | 2'-4 1/2" | 2'-8 1/2" | 3'-0 1/2" | 3'-4 1/2" | 4'-0 1/2" | 4'-8 1/2" | 5'-4 1/2" | 6'-0 1/2" | R.O. W. |
| | 32" | 32" | 36" | 36" | 48" | 48" | | | | Radius |
| | 25" | 26 7/16" | | 31 3/16" | 41 9/16" | | | | | Cord H. |
| (see each) (see each) |  | | | | | | | | | |
| | Gothic Grille Pattern | | | | | | | | | |
| |  | | | | | | | | | |
| | Colonial Grille Pattern | | | | | | | | | |
| |  | | | | | | | | | |
| | Spoke Grille Pattern | | | | | | | | | |
| |  | | | | | | | | | |
| | Gothic Window | | | | | | | | | |
| | CCG2012 | CCG2416 | CCG3220 | CCG4420 | | | | | | Call Size |
| | 24" | 28" | 36" | 48" | | | | | | Unit W. |
| | 41" | 46 7/16" | 55 3/16" | 65 9/16" | | | | | | Unit H. |
| | 2'-0 1/2" | 2'-4 1/2" | 3'-0 1/2" | 4'-0 1/2" | | | | | | R.O. W. |
| | 3'-5 1/2" | 3'-10 15/16" | 4'-7 11/16" | 5'-6 1/16" | | | | | | R.O.H. |



- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4". Specified in inches.
- Unit / Frame Height = Shoulder Height + Cord Height. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Shoulder Height is the height of the straight vertical portion of the unit. Match the shoulder height to the unit height of other non-radius products for side mulling.
- Cord Height is the height of the curved top portion of the window.
- The Radius is the arc of the curved portion of the window.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

| Call Height - DH Call Height - FX Shoulder Height 0" | Eyebrow Window | | | | | | | | | | |
|---|----------------|-----------|-----------|-----------|--|-----------|-----------|-----------|-----------|-----------|---------|
| | 20 | 24 | 28 | 32 | 36 | 44 | 52 | 60 | 68 | Call W. | |
| | 24" | 28" | 32" | 36" | 40" | 48" | 56" | 64" | 72" | | Unit W. |
| | 2'-0 1/2" | 2'-4 1/2" | 2'-8 1/2" | 3'-0 1/2" | 3'-4 1/2" | 4'-0 1/2" | 4'-8 1/2" | 5'-4 1/2" | 6'-0 1/2" | | R.O. W. |
| | | | | | 28" | 32" | 36" | 42" | | Radius | |
| | | | | | 13 9/16" | 16 1/2" | 19 1/2" | 20 3/8" | | Cord H. | |
| | | | | |  | | | | | | |
| | | | | |  | | | | | | |
| | | | | | CDE44 | CDE52 | CDE60 | CDE68 | | Call Size | |
| | | | | | 48" | 56" | 64" | 72" | | Unit W. | |
| | | | | | 13 9/16" | 16 1/2" | 19 1/2" | 20 3/8" | | Unit H. | |
| | | | | | 4'-0 1/2" | 4'-8 1/2" | 5'-4 1/2" | 6'-0 1/2" | | R.O. W. | |
| | | | | | 1'-2 1/16" | 1'-5" | 1'-8" | 1'-8 7/8" | | R.O.H. | |

| Call Height - DH Call Height - FX Shoulder Height (see each) (see each) | Gothic Window | | | | | | | | | | |
|---|--|--------------|---------------------|---------------------|-----------|---------------------|-----------|-----------|-----------|---|---------|
| | 20 | 24 | 28 | 32 | 36 | 44 | 52 | 60 | 68 | Call W. | |
| | 24" | 28" | 32" | 36" | 40" | 48" | 56" | 64" | 72" | | Unit W. |
| | 2'-0 1/2" | 2'-4 1/2" | 2'-8 1/2" | 3'-0 1/2" | 3'-4 1/2" | 4'-0 1/2" | 4'-8 1/2" | 5'-4 1/2" | 6'-0 1/2" | | R.O. W. |
| 32" | 32" | 36" | 36" | 48" | | | | | | Radius | |
| 25" | 26 7/16" | | 31 3/16" | 41 9/16" | | | | | | Cord H. | |
| | 12 C.H. 16" S.H. | | 16 C.H. 20" S.H. | 20 C.H. 24" S.H. | | 20 C.H. 24" S.H. | | | | | |
| |  | | | | | | | | | | |
| |  | | | | | | | | | | |
| |  | | | | | | | | | | |
| | | | | | | | | | |  | |
| | CDG2012 | CDG2416 | CDG3220 | CDG4420 | | | | | | Call Size | |
| | 24" | 28" | 36" | 48" | | | | | | Unit W. | |
| | 41" | 46 7/16" | 55 3/16" | 65 9/16" | | | | | | Unit H. | |
| | 2'-0 1/2" | 2'-4 1/2" | 3'-0 1/2" | 4'-0 1/2" | | | | | | R.O. W. | |
| | 3'-5 1/2" | 3'-10 15/16" | 4'-7 11/16" | 5'-6 1/16" | | | | | | R.O.H. | |