



Quarter Round Top Sizes

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4". Specified in inches.
- Unit / Frame Height = Shoulder Height + Cord Height. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Shoulder Height is the height of the straight vertical portion of the unit. Match the shoulder height to the unit height of other non-radius products for side mulling.
- Cord Height is the height of the curved top portion of the window.
- The Radius is the arc of the curved portion of the window.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH	20	24	28	32	36	44	52	60	68	Call W.
Call Height - FX	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
Shoulder Height	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Radius
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Cord H.
0"	<p>Colonial Grille Pattern</p>									
	<p>Spoke Grille Pattern</p>									
	<p>Sunburst Grille Pattern</p>									
	CCQR20	CCQR24	CCQR28	CCQR32		CCQR44		CCQR68		Call Size
	24"	28"	32"	36"		48"		72"		Unit W.
	24"	28"	32"	36"		48"		72"		Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"		4'-0 1/2"		6'-0 1/2"		R.O. W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"		4'-0 1/2"		6'-0 1/2"		R.O.H.



Quarter Round Top Sizes

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4". Specified in inches.
- Unit / Frame Height = Shoulder Height + Cord Height. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Shoulder Height is the height of the straight vertical portion of the unit. Match the shoulder height to the unit height of other non-radius products for side mulling.
- Cord Height is the height of the curved top portion of the window.
- The Radius is the arc of the curved portion of the window.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH	20	24	28	32	36	44	52	60	68	Call W.
Call Height - FX	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
Shoulder Height	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Radius
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Cord H.

0"	Colonial Grille Pattern						Spoke Grille Pattern		Sunburst Grille Pattern	
	CDQR20	CDQR24	CDQR28	CDQR32	CDQR44	CDQR68				
	24"	28"	32"	36"	48"	72"				
	24"	28"	32"	36"	48"	72"				
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	4'-0 1/2"	6'-0 1/2"				
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	4'-0 1/2"	6'-0 1/2"				