




# Round Top Sizes: Colonial Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height	20	24	28	32	36	44	52	60	68	Call W.
Shoulder H.	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
1"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	12"	14"	16"	18"	20"	24"	28"	32"	36"	Radius
20"										Call Size
24"	CCR20 24" 13"	CCR24 28" 15"	CCR28 32" 17"	CCR32 36" 19"	CCR36 40" 21"	CCR44 48" 25"	CCR52 56" 29"	CCR60 64" 33"	CCR68 72" 37"	Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.
36"										Call Size
40"	CCXR2020 24" 36"	CCXR2420 28" 38"	CCXR2820 32" 40"	CCXR3220 36" 42"	CCXR3620 40" 44"	CCXR4420 48" 48"	CCXR5220 56" 52"	CCXR6020 64" 56"	CCXR6820 72" 60"	Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	3'-0 1/2"	3'-2 1/2"	3'-4 1/2"	3'-6 1/2"	3'-8 1/2"	4'-0 1/2"	4'-4 1/2"	4'-8 1/2"	5'-0 1/2"	R.O.H.
44"										Call Size
48"	CCXR2036 24" 52"	CCXR2436 28" 54"	CCXR2836 32" 56"	CCXR3236 36" 58"	CCXR3636 40" 60"	CCXR4436 48" 64"	CCXR5236 56" 68"	CCXR6036 64" 72"		Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	4'-4 1/2"	4'-6 1/2"	4'-8 1/2"	4'-10 1/2"	5'-0 1/2"	5'-4 1/2"	5'-8 1/2"	6'-0 1/2"		R.O.H.
52"										Call Size
56"	CCXR2044 24" 60"	CCXR2444 28" 62"	CCXR2844 32" 64"	CCXR3244 36" 66"	CCXR3644 40" 68"	CCXR4444 48" 72"	CCXR5244 56" 76"	CCXR6044 64" 80"		Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	5'-0 1/2"	5'-2 1/2"	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"		R.O.H.
59"										Call Size
63"	CCXR2048 24" 64"	CCXR2448 28" 66"	CCXR2848 32" 68"	CCXR3248 36" 70"	CCXR3648 40" 72"	CCXR4448 48" 76"	CCXR5248 56" 80"			Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"			R.O. W.
	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	5'-10 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"			R.O.H.
64"										Call Size
68"	CCXR2055 24" 71"	CCXR2455 28" 73"	CCXR2855 32" 75"	CCXR3255 36" 77"	CCXR3655 40" 79"					Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"					R.O. W.
	5'-11 1/2"	6'-1 1/2"	6'-3 1/2"	6'-5 1/2"	6'-7 1/2"					R.O.H.
<b>Grille Patterns</b>										
	CCXR2060 24" 76"	CCXR2460 28" 78"								Call Size
	2'-0 1/2"	2'-4 1/2"								Unit W.
	6'-0 1/2"	6'-6 1/2"								R.O. W.






# Round Top Sizes: Spoke Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height	20	24	28	32	36	44	52	60	68	Call W.
Shoulder H.	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
1"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	12"	14"	16"	18"	20"	24"	28"	32"	36"	Radius
20"										Call Size
24"	CCR20 24" 13"	CCR24 28" 15"	CCR28 32" 17"	CCR32 36" 19"	CCR36 40" 21"	CCR44 48" 25"	CCR52 56" 29"	CCR60 64" 33"	CCR68 72" 37"	Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.
36"										Call Size
40"	CCXR2020 24" 36"	CCXR2420 28" 38"	CCXR2820 32" 40"	CCXR3220 36" 42"	CCXR3620 40" 44"	CCXR4420 48" 48"	CCXR5220 56" 52"	CCXR6020 64" 56"	CCXR6820 72" 60"	Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	3'-0 1/2"	3'-2 1/2"	3'-4 1/2"	3'-6 1/2"	3'-8 1/2"	4'-0 1/2"	4'-4 1/2"	4'-8 1/2"	5'-0 1/2"	R.O.H.
44"										Call Size
48"	CCXR2036 24" 52"	CCXR2436 28" 54"	CCXR2836 32" 56"	CCXR3236 36" 58"	CCXR3636 40" 60"	CCXR4436 48" 64"	CCXR5236 56" 68"	CCXR6036 64" 72"		Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	4'-4 1/2"	4'-6 1/2"	4'-8 1/2"	4'-10 1/2"	5'-0 1/2"	5'-4 1/2"	5'-8 1/2"	6'-0 1/2"		R.O.H.
48"										Call Size
52"	CCXR2044 24" 60"	CCXR2444 28" 62"	CCXR2844 32" 64"	CCXR3244 36" 66"	CCXR3644 40" 68"	CCXR4444 48" 72"	CCXR5244 56" 76"	CCXR6044 64" 80"		Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	5'-0 1/2"	5'-2 1/2"	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"		R.O.H.
55"										Call Size
59"	CCXR2048 24" 64"	CCXR2448 28" 66"	CCXR2848 32" 68"	CCXR3248 36" 70"	CCXR3648 40" 72"	CCXR4448 48" 76"	CCXR5248 56" 80"			Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"			R.O. W.
	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	5'-10 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"			R.O.H.
60"										Call Size
64"	CCXR2055 24" 71"	CCXR2455 28" 73"	CCXR2855 32" 75"	CCXR3255 36" 77"	CCXR3655 40" 79"					Unit W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"					R.O. W.
	5'-11 1/2"	6'-1 1/2"	6'-3 1/2"	6'-5 1/2"	6'-7 1/2"					R.O.H.
										Call Size
	CCXR2060 24" 76"	CCXR2460 28" 78"								Unit W.
	2'-0 1/2"	2'-4 1/2"								R.O. W.
	6'-0 1/2"	6'-6 1/2"								R.O.H.



### Grille Patterns






# Round Top Sizes: Sunburst Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height	20	24	28	32	36	44	52	60	68	Call W.
Shoulder H.	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
1"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	12"	14"	16"	18"	20"	24"	28"	32"	36"	Radius
20										Call Size
24"	CCR20	CCR24	CCR28	CCR32	CCR36	CCR44	CCR52	CCR60	CCR68	Unit W.
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.
	13"	15"	17"	19"	21"	25"	29"	33"	37"	R.O. W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O.H.
	1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"		
36										Call Size
40"	CCXR2036	CCXR2436	CCXR2836	CCXR3236	CCXR3636	CCXR4436	CCXR5236	CCXR6036		Unit W.
	24"	28"	32"	36"	40"	48"	56"	64"		Unit H.
	36"	38"	40"	42"	44"	48"	52"	56"	60"	R.O. W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O.H.
	4'-4 1/2"	4'-6 1/2"	4'-8 1/2"	4'-10 1/2"	5'-0 1/2"	5'-4 1/2"	5'-8 1/2"	6'-0 1/2"		
44										Call Size
48"	CCXR2044	CCXR2444	CCXR2844	CCXR3244	CCXR3644	CCXR4444	CCXR5244	CCXR6044		Unit W.
	24"	28"	32"	36"	40"	48"	56"	64"		Unit H.
	60"	62"	64"	66"	68"	72"	76"	80"		R.O. W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O.H.
	5'-0 1/2"	5'-2 1/2"	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"		
48										Call Size
52"	CCXR2048	CCXR2448	CCXR2848	CCXR3248	CCXR3648	CCXR4448	CCXR5248			Unit W.
	24"	28"	32"	36"	40"	48"	56"			Unit H.
	64"	66"	68"	70"	72"	76"	80"			R.O. W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"			R.O.H.
	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	5'-10 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"			
55										Call Size
59"	CCXR2055	CCXR2455	CCXR2855	CCXR3255	CCXR3655					Unit W.
	24"	28"	32"	36"	40"					Unit H.
	71"	73"	75"	77"	79"					R.O. W.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"					R.O.H.
	5'-11 1/2"	6'-1 1/2"	6'-3 1/2"	6'-5 1/2"	6'-7 1/2"					
60										Call Size
64"	CCXR2060	CCXR2460								Unit W.
	24"	28"								Unit H.
	76"	78"								R.O. W.
	2'-0 1/2"	2'-4 1/2"								R.O.H.
	6'-0 1/2"	6'-6 1/2"								



### Grille Patterns






# Round Top Sizes: Gothic Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height	20	24	28	32	36	44	52	60	68	Call W.	
Shoulder H.	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.	
1"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.	
	12"	14"	16"	18"	20"	24"	28"	32"	36"	Radius	
20"										Call Size	
24"	CCR20	CCR24	CCR28	CCR32	CCR36	CCR44	CCR52	CCR60	CCR68	Unit W.	
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.	
	13"	15"	17"	19"	21"	25"	29"	33"	37"	R.O. W.	
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. H.	
	1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"		
36"										Call Size	
40"	CCXR2020	CCXR2420	CCXR2820	CCXR3220	CCXR3620	CCXR4420	CCXR5220	CCXR6020	CCXR6820	Unit W.	
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.	
	36"	38"	40"	42"	44"	48"	52"	56"	60"	R.O. W.	
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. H.	
	3'-0 1/2"	3'-2 1/2"	3'-4 1/2"	3'-6 1/2"	3'-8 1/2"	4'-0 1/2"	4'-4 1/2"	4'-8 1/2"	5'-0 1/2"		
44"										Call Size	
48"	CCXR2036	CCXR2436	CCXR2836	CCXR3236	CCXR3636	CCXR4436	CCXR5236	CCXR6036	CCXR6836	Unit W.	
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.	
	52"	54"	56"	58"	60"	64"	68"	72"	76"	R.O. W.	
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. H.	
	4'-4 1/2"	4'-6 1/2"	4'-8 1/2"	4'-10 1/2"	5'-0 1/2"	5'-4 1/2"	5'-8 1/2"	6'-0 1/2"	6'-4 1/2"		
48"										Call Size	
52"	CCXR2044	CCXR2444	CCXR2844	CCXR3244	CCXR3644	CCXR4444	CCXR5244	CCXR6044	CCXR6844	Unit W.	
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.	
	60"	62"	64"	66"	68"	72"	76"	80"	84"	R.O. W.	
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. H.	
	5'-0 1/2"	5'-2 1/2"	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"	7'-0 1/2"		
55"										Call Size	
59"	CCXR2048	CCXR2448	CCXR2848	CCXR3248	CCXR3648	CCXR4448	CCXR5248	CCXR6048	CCXR6848	Unit W.	
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.	
	64"	66"	68"	70"	72"	76"	80"	84"	88"	R.O. W.	
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. H.	
	5'-4 1/2"	5'-6 1/2"	5'-8 1/2"	5'-10 1/2"	6'-0 1/2"	6'-4 1/2"	6'-8 1/2"	7'-0 1/2"	7'-4 1/2"		
60"										Call Size	
64"	CCXR2055	CCXR2455	CCXR2855	CCXR3255	CCXR3655	CCXR4455	CCXR5255	CCXR6055	CCXR6855	Unit W.	
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit H.	
	71"	73"	75"	77"	79"	83"	87"	91"	95"	R.O. W.	
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. H.	
	5'-11 1/2"	6'-1 1/2"	6'-3 1/2"	6'-5 1/2"	6'-7 1/2"	7'-0 1/2"	7'-2 1/2"	7'-4 1/2"	7'-6 1/2"		
<b>Grille Patterns</b>											
	CCXR2060	CCXR2460									Call Size
	24"	28"									Unit W.
	76"	78"									Unit H.
	2'-0 1/2"	2'-4 1/2"									R.O. W.
	6'-0 1/2"	6'-6 1/2"									R.O. H.






# Round Top Sizes: Extra Wide Units


- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Call Height + 4". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be muller with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH	76	80	92	Call W.
	80"	84"	96"	Unit W.
	6'-8 1/2"	7'-0 1/2"	8'-0 1/2"	R.O. W.
	40"	42"	48"	Radius
	1"			


  



10






11






12




**Colonial Grille Pattern**




**Lexington Grille Pattern**

**Spoke Grille Pattern**

**Sunburst Grille Pattern**

**Gothic Grille Pattern**


CCR76	CCR80	CCR92	Call Size
80"	84"	96"	Unit W.
41"	43"	49"	Unit H.
6'-8 1/2"	7'-0 1/2"	8'-0 1/2"	R.O. W.
3'-5 1/2"	3'-7 1/2"	4'-1 1/2"	R.O.H.



# Round Top Sizes: Colonial Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH Call Height - FX Shoulder Height	Call Width										Call W.
	20	24	28	32	36	44	52	60	68		Unit W.
1"											
	CDR20	CDR24	CDR28	CDR32	CDR36	CDR44	CDR52	CDR60	CDR68		Call Size
	24"	28"	32"	36"	40"	48"	56"	64"	72"		Unit W.
	13"	15"	17"	19"	21"	25"	29"	33"	37"		Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"		R.O. W.
	1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"		R.O.H.
14"											
30 3/16"	CDXR2030 <sup>3/16</sup>	CDXR2430 <sup>3/16</sup>	CDXR2830 <sup>3/16</sup>	CDXR3230 <sup>3/16</sup>	CDXR3630 <sup>3/16</sup>	CDXR4430 <sup>3/16</sup>	CDXR5230 <sup>3/16</sup>	CDXR6030 <sup>3/16</sup>	CDXR6830 <sup>3/16</sup>		Call Size
34 3/16"	24"	28"	32"	36"	40"	48"	56"	64"	72"		Unit W.
	46 3/16"	48 3/16"	50 3/16"	52 3/16"	54 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"		Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"		R.O. W.
	3'-10 11/16"	4'-0 11/16"	4'-2 11/16"	4'-4 11/16"	4'-6 11/16"	4'-10 11/16"	5'-2 11/16"	5'-6 11/16"	5'-10 11/16"		R.O.H.
20"											
42 3/16"	CDXR2042 <sup>3/16</sup>	CDXR2442 <sup>3/16</sup>	CDXR2842 <sup>3/16</sup>	CDXR3242 <sup>3/16</sup>	CDXR3642 <sup>3/16</sup>	CDXR4442 <sup>3/16</sup>	CDXR5242 <sup>3/16</sup>	CDXR6042 <sup>3/16</sup>			Call Size
46 3/16"	24"	28"	32"	36"	40"	48"	56"	64"			Unit W.
	58 3/16"	60 3/16"	62 3/16"	64 3/16"	66 3/16"	70 3/16"	74 3/16"	78 3/16"			Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"			R.O. W.
	4'-10 11/16"	5'-0 11/16"	5'-2 11/16"	5'-4 11/16"	5'-6 11/16"	5'-10 11/16"	6'-2 11/16"	6'-6 11/16"			R.O.H.
24"											
50 3/16"	CDXR2050 <sup>3/16</sup>	CDXR2450 <sup>3/16</sup>	CDXR2850 <sup>3/16</sup>	CDXR3250 <sup>3/16</sup>	CDXR3650 <sup>3/16</sup>	CDXR4450 <sup>3/16</sup>					Call Size
54 3/16"	24"	28"	32"	36"	40"	48"					Unit W.
	66 3/16"	68 3/16"	70 3/16"	72 3/16"	74 3/16"	78 3/16"					Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"					R.O. W.
	5'-6 11/16"	5'-8 11/16"	5'-10 11/16"	6'-0 11/16"	6'-2 11/16"	6'-6 11/16"					R.O.H.
28"											
58 3/16"	CDXR2058 <sup>3/16</sup>	CDXR2458 <sup>3/16</sup>	CDXR2858 <sup>3/16</sup>								Call Size
62 3/16"	24"	28"	32"								Unit W.
	74 3/16"	76 3/16"	78 3/16"								Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"								R.O. W.
	6'-2 11/16"	6'-4 11/16"	6'-6 11/16"								R.O.H.



### Grille Patterns






# Round Top Sizes: Spoke Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH Call Height - FX Shoulder Height	Call Width									Call W.
	20	24	28	32	36	44	52	60	68	Unit W.
1"										
	CDR20	CDR24	CDR28	CDR32	CDR36	CDR44	CDR52	CDR60	CDR68	Call Size
	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
	13"	15"	17"	19"	21"	25"	29"	33"	37"	Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.
14"										
30 3/16"	CDXR2030 <sup>3/16</sup>	CDXR2430 <sup>3/16</sup>	CDXR2830 <sup>3/16</sup>	CDXR3230 <sup>3/16</sup>	CDXR3630 <sup>3/16</sup>	CDXR4430 <sup>3/16</sup>	CDXR5230 <sup>3/16</sup>	CDXR6030 <sup>3/16</sup>	CDXR6830 <sup>3/16</sup>	Call Size
34 3/16"	24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
	46 3/16"	48 3/16"	50 3/16"	52 3/16"	54 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	3'-10 11/16"	4'-0 11/16"	4'-2 11/16"	4'-4 11/16"	4'-6 11/16"	4'-10 11/16"	5'-2 11/16"	5'-6 11/16"	5'-10 11/16"	R.O.H.
20"										
42 3/16"	CDXR2042 <sup>3/16</sup>	CDXR2442 <sup>3/16</sup>	CDXR2842 <sup>3/16</sup>	CDXR3242 <sup>3/16</sup>	CDXR3642 <sup>3/16</sup>	CDXR4442 <sup>3/16</sup>	CDXR5242 <sup>3/16</sup>	CDXR6042 <sup>3/16</sup>		Call Size
46 3/16"	24"	28"	32"	36"	40"	48"	56"	64"		Unit W.
	58 3/16"	60 3/16"	62 3/16"	64 3/16"	66 3/16"	70 3/16"	74 3/16"	78 3/16"		Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"		R.O. W.
	4'-10 11/16"	5'-0 11/16"	5'-2 11/16"	5'-4 11/16"	5'-6 11/16"	5'-10 11/16"	6'-2 11/16"	6'-6 11/16"		R.O.H.
24"										
50 3/16"	CDXR2050 <sup>3/16</sup>	CDXR2450 <sup>3/16</sup>	CDXR2850 <sup>3/16</sup>	CDXR3250 <sup>3/16</sup>	CDXR3650 <sup>3/16</sup>	CDXR4450 <sup>3/16</sup>				Call Size
54 3/16"	24"	28"	32"	36"	40"	48"				Unit W.
	66 3/16"	68 3/16"	70 3/16"	72 3/16"	74 3/16"	78 3/16"				Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"				R.O. W.
	5'-6 11/16"	5'-8 11/16"	5'-10 11/16"	6'-0 11/16"	6'-2 11/16"	6'-6 11/16"				R.O.H.
28"										
58 3/16"	CDXR2058 <sup>3/16</sup>	CDXR2458 <sup>3/16</sup>	CDXR2858 <sup>3/16</sup>							Call Size
62 3/16"	24"	28"	32"							Unit W.
	74 3/16"	76 3/16"	78 3/16"							Unit H.
	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"							R.O. W.
	6'-2 11/16"	6'-4 11/16"	6'-6 11/16"							R.O.H.



### Grille Patterns






# Round Top Sizes: Sunburst Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH	Call Height - FX	Shoulder Height	20	24	28	32	36	44	52	60	68	Call W.
			24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
			12"	14"	16"	18"	20"	24"	28"	32"	36"	Radius
1"												
			CDR20	CDR24	CDR28	CDR32	CDR36	CDR44	CDR52	CDR60	CDR68	Call Size
			24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
			13"	15"	17"	19"	21"	25"	29"	33"	37"	Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
			1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.
14"	30 3/16"	34 3/16"										
			CDXR2030 <sup>3/16</sup>	CDXR2430 <sup>3/16</sup>	CDXR2830 <sup>3/16</sup>	CDXR3230 <sup>3/16</sup>	CDXR3630 <sup>3/16</sup>	CDXR4430 <sup>3/16</sup>	CDXR5230 <sup>3/16</sup>	CDXR6030 <sup>3/16</sup>	CDXR6830 <sup>3/16</sup>	Call Size
			24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
			46 3/16"	48 3/16"	50 3/16"	52 3/16"	54 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
			3'-10 11/16"	4'-0 11/16"	4'-2 11/16"	4'-4 11/16"	4'-6 11/16"	4'-10 11/16"	5'-2 11/16"	5'-6 11/16"	5'-10 11/16"	R.O.H.
20"	42 3/16"	46 3/16"										
			CDXR2042 <sup>3/16</sup>	CDXR2442 <sup>3/16</sup>	CDXR2842 <sup>3/16</sup>	CDXR3242 <sup>3/16</sup>	CDXR3642 <sup>3/16</sup>	CDXR4442 <sup>3/16</sup>	CDXR5242 <sup>3/16</sup>	CDXR6042 <sup>3/16</sup>		Call Size
			24"	28"	32"	36"	40"	48"	56"	64"		Unit W.
			58 3/16"	60 3/16"	62 3/16"	64 3/16"	66 3/16"	70 3/16"	74 3/16"	78 3/16"		Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"		R.O. W.
			4'-10 11/16"	5'-0 11/16"	5'-2 11/16"	5'-4 11/16"	5'-6 11/16"	5'-10 11/16"	6'-2 11/16"	6'-6 11/16"		R.O.H.
24"	50 3/16"	54 3/16"										
			CDXR2050 <sup>3/16</sup>	CDXR2450 <sup>3/16</sup>	CDXR2850 <sup>3/16</sup>	CDXR3250 <sup>3/16</sup>	CDXR3650 <sup>3/16</sup>	CDXR4450 <sup>3/16</sup>				Call Size
			24"	28"	32"	36"	40"	48"				Unit W.
			66 3/16"	68 3/16"	70 3/16"	72 3/16"	74 3/16"	78 3/16"				Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"				R.O. W.
			5'-6 11/16"	5'-8 11/16"	5'-10 11/16"	6'-0 11/16"	6'-2 11/16"	6'-6 11/16"				R.O.H.
28"	58 3/16"	62 3/16"										
			CDXR2058 <sup>3/16</sup>	CDXR2458 <sup>3/16</sup>	CDXR2858 <sup>3/16</sup>							Call Size
			24"	28"	32"							Unit W.
			74 3/16"	76 3/16"	78 3/16"							Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"							R.O. W.
			6'-2 11/16"	6'-4 11/16"	6'-6 11/16"							R.O.H.



### Grille Patterns






# Round Top Sizes: Gothic Grille

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH	Call Height - FX	Shoulder Height	20	24	28	32	36	44	52	60	68	Call W.
			24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
			12"	14"	16"	18"	20"	24"	28"	32"	36"	Radius
1"												
			CDR20	CDR24	CDR28	CDR32	CDR36	CDR44	CDR52	CDR60	CDR68	Call Size
			24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
			13"	15"	17"	19"	21"	25"	29"	33"	37"	Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
			1'-1 1/2"	1'-3 1/2"	1'-5 1/2"	1'-7 1/2"	1'-9 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.
14"	30 3/16"	34 3/16"										
			CDXR2030 <sup>3/16</sup>	CDXR2430 <sup>3/16</sup>	CDXR2830 <sup>3/16</sup>	CDXR3230 <sup>3/16</sup>	CDXR3630 <sup>3/16</sup>	CDXR4430 <sup>3/16</sup>	CDXR5230 <sup>3/16</sup>	CDXR6030 <sup>3/16</sup>	CDXR6830 <sup>3/16</sup>	Call Size
			24"	28"	32"	36"	40"	48"	56"	64"	72"	Unit W.
			46 3/16"	48 3/16"	50 3/16"	52 3/16"	54 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
			3'-10 11/16"	4'-0 11/16"	4'-2 11/16"	4'-4 11/16"	4'-6 11/16"	4'-10 11/16"	5'-2 11/16"	5'-6 11/16"	5'-10 11/16"	R.O.H.
20"	42 3/16"	46 3/16"										
			CDXR2042 <sup>3/16</sup>	CDXR2442 <sup>3/16</sup>	CDXR2842 <sup>3/16</sup>	CDXR3242 <sup>3/16</sup>	CDXR3642 <sup>3/16</sup>	CDXR4442 <sup>3/16</sup>	CDXR5242 <sup>3/16</sup>	CDXR6042 <sup>3/16</sup>		Call Size
			24"	28"	32"	36"	40"	48"	56"	64"		Unit W.
			58 3/16"	60 3/16"	62 3/16"	64 3/16"	66 3/16"	70 3/16"	74 3/16"	78 3/16"		Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"		R.O. W.
			4'-10 11/16"	5'-0 11/16"	5'-2 11/16"	5'-4 11/16"	5'-6 11/16"	5'-10 11/16"	6'-2 11/16"	6'-6 11/16"		R.O.H.
24"	50 3/16"	54 3/16"										
			CDXR2050 <sup>3/16</sup>	CDXR2450 <sup>3/16</sup>	CDXR2850 <sup>3/16</sup>	CDXR3250 <sup>3/16</sup>	CDXR3650 <sup>3/16</sup>	CDXR4450 <sup>3/16</sup>				Call Size
			24"	28"	32"	36"	40"	48"				Unit W.
			66 3/16"	68 3/16"	70 3/16"	72 3/16"	74 3/16"	78 3/16"				Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"				R.O. W.
			5'-6 11/16"	5'-8 11/16"	5'-10 11/16"	6'-0 11/16"	6'-2 11/16"	6'-6 11/16"				R.O.H.
28"	58 3/16"	62 3/16"										
			CDXR2058 <sup>3/16</sup>	CDXR2458 <sup>3/16</sup>	CDXR2858 <sup>3/16</sup>							Call Size
			24"	28"	32"							Unit W.
			74 3/16"	76 3/16"	78 3/16"							Unit H.
			2'-0 1/2"	2'-4 1/2"	2'-8 1/2"							R.O. W.
			6'-2 11/16"	6'-4 11/16"	6'-6 11/16"							R.O.H.



### Grille Patterns






# Round Top Sizes: Extra Wide Units


- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height - DH	Call Height - FX	Shoulder Height	<b>76</b>	<b>80</b>	<b>92</b>	Call W.
			80"	84"	96"	Unit W.
			6'-8 1/2"	7'-0 1/2"	8'-0 1/2"	R.O. W.
			40"	42"	48"	Radius
			1"			


  



10






11






12




**Colonial Grille Pattern**




**Lexington Grille Pattern**

**Spoke Grille Pattern**

**Sunburst Grille Pattern**

**Gothic Grille Pattern**

<b>CDR76</b>	<b>CDR80</b>	<b>CDR92</b>	Call Size
80"	84"	96"	Unit W.
41"	43"	49"	Unit H.
6'-8 1/2"	7'-0 1/2"	8'-0 1/2"	R.O. W.
3'-5 1/2"	3'-7 1/2"	4'-1 1/2"	R.O.H.



# Round Top Sizes for Inswing & True French Doors

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
4. Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
7. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
8. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
9. Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
10. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
11. Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

## Round Tops

Call Height Unit/Frame H. Shoulder H.	20 3/8	26 3/8	28 3/8	32 3/8	35 3/8	44	56	60	68	Call W.
	1"	2-0	2-6	2-8	3-0	3-3	4-0	5-0	5-4	6-0
	24 3/8"	30 3/8"	32 3/8"	36 3/8"	39 3/8"	48"	60"	64"	72"	Unit/Frame W.
	2'-0 7/8"	2'-6 7/8"	2'-8 7/8"	3'-0 7/8"	3'-3 7/8"	4'-0 1/2"	5'-0 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.
	CIR20-3/8	CIR26-3/8	CIR28-3/8	CIR32-3/8	CIR44	CIR52	CIR60	CIR68	Call Size	
	48"	56"	64"	72"	48"	56"	64"	72"	Unit W.	
	25"	29"	33"	37"	25"	29"	33"	37"	Unit H.	
	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. W.	
	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.	