








Stock Tempered Glass Fixed Lites

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
4. Unit / Frame Height = Call Height + 4". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
7. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
8. Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
9. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
10. Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height	Unit/Frame Height	R.O. Height	17 1/16	25 3/4	29 7/16	41 1/16	Call W.
17 1/16	21 1/16"	1'-9 9/16"					Unit W.
25 3/4	29 3/4"	2'-6 1/4"					R.O. W.
29 7/16	33 7/16"	2'-9 15/16"					
41 1/16	45 11/16"	3'-9 9/16"					

<p>17 1/16 21 1/16" 1'-9 9/16"</p>	 <p>4</p>
<p>25 3/4 29 3/4" 2'-6 1/4"</p>	 <p>3</p>
<p>29 7/16 33 7/16" 2'-9 15/16"</p>	 <p>2</p>
<p>41 1/16 45 11/16" 3'-9 9/16"</p>	 <p>5</p>
<p>41 1/16 45 11/16" 3'-9 9/16"</p>	 <p>1</p>