



- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
- Unit / Frame Height = Call Height + 4". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Clear Opening (egress), Glass Sizes and additional dimensions are available on the Dimensions page at the back of this section.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 6-9/16". Specify exact jamb depth needed.
- Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.

Call Height	28	32	36	44	48	55	60	68	Call Width
Unit/Frame Height	32"	36"	40"	48"	52"	59"	64"	72"	Unit/Frame Width
R.O. Height	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	4'-0 1/2"	4'-4 1/2"	4'-11 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. Width
12	1	7	14	21	28	31	34	37	
16	2	8	15	22	29	32	35	38	
20	3	9	16	23	30	33	36	39	
24	4	10	17	24					
26	5	11	18	25					
28	6	12	19	26					
32		13	20	27					

Available Grille Patterns



No Grille



Colonial



Lexington

Min. Call W. = 20
Min. Call H. = 20