



# SH57 Tilt Single Hung Sizes: 1-wide

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 3-3/8" x Qty wide + Mull Gain (1/16" per mull). Specified in inches.
- Unit / Frame Height = (Call Height x 2) + 4-5/8". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness). Specify which jamb depth needed.
- Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - SH/DH	16	20	24	28	32	36	40	Call Width
14	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
16	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
20	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
22	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
24	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
28	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
32	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
34	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	Unit/Frame Width
Call Height - FX	30	32 5/8"	34	36 5/8"	38 1/8"	40 3/8"	42 5/8"	Call Height
Unit/Frame Height	32 5/8"	34 1/8"	36 5/8"	38 1/8"	40 3/8"	42 5/8"	44 1/8"	Unit/Frame Height
R.O. Height	2'-9 1/8"	3'-1 1/8"	3'-3 1/8"	3'-5 1/8"	3'-7 1/8"	3'-9 1/8"	3'-11 1/8"	R.O. Height
R.O. Width	1'-7 7/8"	1'-11 7/8"	2'-3 7/8"	2'-7 7/8"	2'-11 7/8"	3'-3 7/8"	3'-7 7/8"	R.O. Width

### Grille Patterns



No Grille



Colonial



Lexington



# SH57 Tilt Single Hung Sizes: 2-wide

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 3-3/8" x Qty wide + Mull Gain (1/16" per mull). Specified in inches.
- Unit / Frame Height = (Call Height x 2) + 4-5/8". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness). Specify which jamb depth needed.
- Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - SH/DH	Call Height - FX	Unit/Frame Height	R.O. Height	16-2	20-2	24-2	28-2	32-2	36-2	40-2	Call Width
				38 13/16"	46 13/16"	54 13/16"	62 13/16"	70 13/16"	78 13/16"	86 13/16"	Unit/Frame Width
				3'-3 7/16"	3'-11 7/16"	4'-7 7/16"	5'-3 7/16"	5'-11 7/16"	6'-7 7/16"	7'-3 7/16"	R.O. Width
14	30	32 5/8"	2'-9 1/8"	57 V57SH1614-2	65 V57SH2014-2	73 V57SH2414-2	81 V57SH2814-2	89 V57SH3214-2	97 V57SH3614-2	105 V57SH4014-2	Grille Patterns  No Grille  Colonial  Lexington
				58 V57SH1616-2	66 V57SH2016-2	74 V57SH2416-2	82 V57SH2816-2	90 V57SH3216-2	98 V57SH3616-2	106 V57SH4016-2	
16	34	36 5/8"	3'-1 1/8"	59 V57SH1620-2	67 V57SH2020-2	75 V57SH2420-2	83 V57SH2820-2	91 V57SH3220-2	99 V57SH3620-2	107 V57SH4020-2	
				60 V57SH1622-2	68 V57SH2022-2	76 V57SH2422-2	84 V57SH2822-2	92 V57SH3222-2	100 V57SH3622-2	108 V57SH4022-2	
20	42	44 5/8"	3'-9 1/8"	61 V57SH1624-2	69 V57SH2024-2	77 V57SH2424-2	85 V57SH2824-2	93 V57SH3224-2	101 V57SH3624-2	109 V57SH4024-2	
				62 V57SH1628-2	70 V57SH2028-2	78 V57SH2428-2	86 V57SH2828-2	94 V57SH3228-2	102 V57SH3628-2	110 V57SH4028-2	
22	46	48 5/8"	4'-1 1/8"	63 V57SH1632-2	71 V57SH2032-2	79 V57SH2432-2	87 V57SH2832-2	95 V57SH3232-2	103 V57SH3632-2	111 V57SH4032-2	
				64 V57SH1634-2	72 V57SH2034-2	80 V57SH2434-2	88 V57SH2834-2	96 V57SH3234-2	104 V57SH3634-2	112 V57SH4034-2	
24	50	52 5/8"	4'-5 1/8"	65 V57SH1640-2	73 V57SH2040-2	81 V57SH2440-2	89 V57SH2840-2	97 V57SH3240-2	105 V57SH3640-2	113 V57SH4040-2	
				66 V57SH1644-2	74 V57SH2044-2	82 V57SH2444-2	90 V57SH2844-2	98 V57SH3244-2	106 V57SH3644-2	114 V57SH4044-2	
28	58	60 5/8"	5'-1 1/8"	67 V57SH1648-2	75 V57SH2048-2	83 V57SH2448-2	91 V57SH2848-2	99 V57SH3248-2	107 V57SH3648-2	115 V57SH4048-2	
				68 V57SH1652-2	76 V57SH2052-2	84 V57SH2452-2	92 V57SH2852-2	100 V57SH3252-2	108 V57SH3652-2	116 V57SH4052-2	
32	66	68 5/8"	5'-9 1/8"	69 V57SH1656-2	77 V57SH2056-2	85 V57SH2456-2	93 V57SH2856-2	101 V57SH3256-2	109 V57SH3656-2	117 V57SH4056-2	
				70 V57SH1660-2	78 V57SH2060-2	86 V57SH2460-2	94 V57SH2860-2	102 V57SH3260-2	110 V57SH3660-2	118 V57SH4060-2	
34	70	72 5/8"	6'-1 1/8"	71 V57SH1664-2	79 V57SH2064-2	87 V57SH2464-2	95 V57SH2864-2	103 V57SH3264-2	111 V57SH3664-2	119 V57SH4064-2	
				72 V57SH1668-2	80 V57SH2068-2	88 V57SH2468-2	96 V57SH2868-2	104 V57SH3268-2	112 V57SH3668-2	120 V57SH4068-2	



# SH57 Tilt Single Hung Sizes: 3-wide

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width = Call Width + 3-3/8" x Qty wide + Mull Gain (1/16" per mull). Specified in inches.
- Unit / Frame Height = (Call Height x 2) + 4-5/8". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- Matching Height Fixed Lite units are referenced in the side column under "Call Height - Fixed Lite".
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness). Specify which jamb depth needed.
- Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - SH/DH	Call Height - FX	Unit/Frame Height	R.O. Height	16-3	20-3	24-3	28-3	32-3	36-3	40-3	Call Width
14	30	32 5/8"	2'-9 1/8"	113 V57SH1614-3	121 V57SH2014-3	129 V57SH2414-3	137 V57SH2814-3	145 V57SH3214-3	153 V57SH3614-3	161 V57SH4014-3	58 1/4"
16	34	36 5/8"	3'-1 1/8"	114 V57SH1616-3	122 V57SH2016-3	130 V57SH2416-3	138 V57SH2816-3	146 V57SH3216-3	154 V57SH3616-3	162 V57SH4016-3	70 1/4"
20	42	44 5/8"	3'-9 1/8"	115 V57SH1620-3	123 V57SH2020-3	131 V57SH2420-3	139 V57SH2820-3	147 V57SH3220-3	155 V57SH3620-3	163 V57SH4020-3	82 1/4"
22	46	48 5/8"	4'-1 1/8"	116 V57SH1622-3	124 V57SH2022-3	132 V57SH2422-3	140 V57SH2822-3	148 V57SH3222-3	156 V57SH3622-3	164 V57SH4022-3	94 1/4"
24	50	52 5/8"	4'-5 1/8"	117 V57SH1624-3	125 V57SH2024-3	133 V57SH2424-3	141 V57SH2824-3	149 V57SH3224-3	157 V57SH3624-3	165 V57SH4024-3	106 1/4"
28	58	60 5/8"	5'-1 1/8"	118 V57SH1628-3	126 V57SH2028-3	134 V57SH2428-3	142 V57SH2828-3	150 V57SH3228-3	158 V57SH3628-3	166 V57SH4028-3	118 1/4"
32	66	68 5/8"	5'-9 1/8"	119 V57SH1632-3	127 V57SH2032-3	135 V57SH2432-3	143 V57SH2832-3	151 V57SH3232-3	159 V57SH3632-3	167 V57SH4032-3	130 1/4"
34	70	72 5/8"	6'-1 1/8"	120 V57SH1634-3	128 V57SH2034-3	136 V57SH2434-3	144 V57SH2834-3	152 V57SH3234-3	160 V57SH3634-3	168 V57SH4034-3	130 1/4"

### Grille Patterns



No Grille



Colonial



Lexington