



PE20 Fixed Lite Sizes: Call Widths 12 to 36

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width for Call Widths < 44 = Call Width + 3 3/8". For Call Widths ≥ 44 = Call Width + 2 15/16". Specified in inches.
4. Unit / Frame Height = Call Height + 2-5/8". Specified in inches.
5. Rough Opening Width for Call Widths < 44 = Unit/Frame Width + 5/8". For Call Widths ≥ 44 = Unit/Frame Width + 9/16". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 3/8". Specified in feet and inches.
7. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
8. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
9. Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
10. The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call Height - SH/DH	Call Height - FX	Unit/Frame Height	R.O. Height	12	16	20	24	28	32	36	Call Width
				15 3/8"	19 3/8"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	Unit/Frame Width
				1'-4"	1'-8"	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	R.O. Width
14	30	32 5/8"	2'-9"	1	9	17	25	33	41	49	
				VF1230	VF1630	VF2030	VF2430	VF2830	VF3230	VF3630	
16	34	36 5/8"	3'-1"	2	10	18	26	34	42	50	
				VF1234	VF1634	VF2034	VF2434	VF2834	VF3234	VF3634	
20	42	44 5/8"	3'-9"	3	11	19	27	35	43	51	
				VF1242	VF1642	VF2042	VF2442	VF2842	VF3242	VF3642	
22	46	48 5/8"	4'-1"	4	12	20	28	36	44	52	
				VF1462	VF1646	VF2046	VF2446	VF2846	VF3246	VF3646	
24	50	52 5/8"	4'-5"	5	13	21	29	37	45	53	
				VF1250	VF1650	VF2050	VF2450	VF2850	VF3250	VF3650	
28	58	60 5/8"	5'-1"	6	14	22	30	38	46	54	
				VF1258	VF1658	VF2058	VF2458	VF2858	VF3258	VF3658	
32	66	68 5/8"	5'-9"	7	15	23	31	39	47	55	
				VF1266	VF1666	VF2066	VF2466	VF2866	VF3266	VF3666	
34	70	72 5/8"	6'-1"	8	16	24	32	40	48	56	
				VF1270	VF1670	VF2070	VF2470	VF2870	VF3270	VF3670	

Grille Patterns



No Grille



Colonial



Lexington



PE20 Fixed Lite Sizes: Call Widths 40 to 68

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width for Call Widths < 44 = Call Width + 3 3/8". For Call Widths ≥ 44 = Call Width + 2 15/16". Specified in inches.
4. Unit / Frame Height = Call Height + 2-5/8". Specified in inches.
5. Rough Opening Width for Call Widths < 44 = Unit/Frame Width + 5/8". For Call Widths ≥ 44 = Unit/Frame Width + 9/16". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 3/8". Specified in feet and inches.
7. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
8. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
9. Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
10. The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call Height - SH/DH	40	44	52	60	68	Call Width
14	43 3/8"	46 15/16"	54 15/16"	62 15/16"	70 15/16"	Unit/Frame Width
16	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	5'-11 1/2"	R.O. Width
Call Height - FX						
30						
32 5/8"						
Unit/Frame Height						
2'-9"						
3'-1"						
3'-9"						
4'-1"						
4'-5"						
5'-1"						
5'-9"						
6'-1"						
R.O. Height						
2'-9"						
3'-1"						
3'-9"						
4'-1"						
4'-5"						
5'-1"						
5'-9"						
6'-1"						

Grille Patterns



No Grille



Colonial



Lexington

	57		65		73		81		89
VF4030		VF4430		VF5230		VF6030		VF6830	
	58		66		74		82		90
VF4034		VF4434		VF5234		VF6034		VF6834	
	59		67		75		83		91
VF4042		VF4442		VF5242		VF6042		VF6842	
	60		68		76		84		92
VF4046		VF4446		VF5246		VF6046		VF6846	
	61		69		77		85		93
VF4050		VF4450		VF5250		VF6050		VF6850	
	62		70		78		86		94
VF4058		VF4458		VF5258		VF6058		VF6858	
	63		71		79		87		95
VF4066		VF4466		VF5266		VF6066		VF6866	
	64		72		80		88		
VF4070		VF4470		VF5270		VF6070			