



# PE20 Stock Tempered Glass Fixed Lites

These units are specially sized to take advantage of the lower cost and quicker delivery of stock tempered glass.

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width for Call Widths < 44 = Call Width + 3 3/8" . For Call Widths ≥ 44 = Call Width + 2 15/16". Specified in inches.
4. Unit / Frame Height = Call Height + 2-5/8". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
7. The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call Height	Unit/Frame Height	R.O. Height	17 9/16	26 1/4	29 15/16	42	Call W.
18 5/16	20 15/16"	1'-10 3/16"	20 15/16"	29 5/8"	33 5/16"	44 15/16"	Unit W.
27	29 5/8"	2'-6 7/8"	1'-9 7/16"	2'-6 1/8"	2'-8 13/16"	3'-9 7/8"	R.O. W.
30 11/16	33 5/16"	2'-10 9/16"					
42 5/16	44 15/16"	3'-10 3/16"					