



PE20 Round Top Sizes

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
- Unit / Frame Width for Call Widths < 44 = Call Width + 3 3/8". For Call Widths ≥ 44 = Call Width + 2 15/16". Specified in inches.
- Unit / Frame Height = Shoulder Height + Radius. Specified in inches.
- Rough Opening Width for Call Widths < 44 = Unit/Frame Width + 5/8". For Call Widths ≥ 44 = Unit/Frame Width + 9/16". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call H. - SH/DH Call H. - SS/FX Shoulder H.	20	24	28	32	36	40	44	52	60	68	Call W.
	1"	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	70 15/16"
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	5'-11 1/2"	R.O. W.
	11 11/16"	13 11/16"	15 11/16"	17 11/16"	19 11/16"	21 11/16"	23 15/32"	27 15/32"	31 15/32"	35 15/32"	Radius
											Call Size
	VR20	VR24	VR28	VR32	VR36	VR40	VR44	VR52	VR60	VR68	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	70 15/16"	Unit W.
	12 11/16"	14 11/16"	16 11/16"	18 11/16"	20 11/16"	22 11/16"	24 15/32"	28 15/32"	32 15/32"	36 15/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	5'-11 1/2"	R.O. W.
	1'-1 3/16"	1'-3 3/16"	1'-5 3/16"	1'-7 3/16"	1'-9 3/16"	1'-11 3/16"	2'-1 1/2"	2'-5 1/2"	2'-9 1/2"	3'-1 1/2"	R.O.H.
20											Call Size
	VXR2020	VXR2420	VXR2820	VXR3220	VXR3620	VXR4020	VXR4420	VXR5220	VXR6020	VXR6820	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	70 15/16"	Unit W.
	34 5/16"	36 5/16"	38 5/16"	40 5/16"	42 5/16"	44 5/16"	46 3/32"	50 3/32"	54 3/32"	58 3/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	5'-11 1/2"	R.O. W.
	2'-10 13/16"	3'-0 13/16"	3'-2 13/16"	3'-4 13/16"	3'-6 13/16"	3'-8 13/16"	3'-10 19/32"	4'-2 19/32"	4'-6 19/32"	4'-10 19/32"	R.O.H.
16											Call Size
	VXR2034	VXR2434	VXR2834	VXR3234	VXR3634	VXR4034	VXR4434	VXR5234	VXR6034	VXR6834	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	70 15/16"	Unit W.
	48 5/16"	50 5/16"	52 5/16"	54 5/16"	56 5/16"	58 5/16"	60 3/32"	64 3/32"	68 3/32"	72 3/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	5'-11 1/2"	R.O. W.
	4'-0 13/16"	4'-2 13/16"	4'-4 13/16"	4'-6 13/16"	4'-8 13/16"	4'-10 13/16"	5'-0 19/32"	5'-4 19/32"	5'-8 19/32"	6'-0 19/32"	R.O.H.
20											Call Size
	VXR2042	VXR2442	VXR2842	VXR3242	VXR3642	VXR4042	VXR4442	VXR5242	VXR6042	No Grille	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	72 3/32"	Unit W.
	56 5/16"	58 5/16"	60 5/16"	62 5/16"	64 5/16"	66 5/16"	68 3/32"	72 3/32"	76 3/32"	80 3/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	6'-0 19/32"	R.O. W.
	4'-8 13/16"	4'-10 13/16"	5'-0 13/16"	5'-2 13/16"	5'-4 13/16"	5'-6 13/16"	5'-8 19/32"	6'-0 19/32"	6'-4 19/32"	6'-8 19/32"	R.O.H.
											Colonial
											Lexington
											Snoke
											Sunburst (shown)
22											Call Size
	VXR2046	VXR2446	VXR2846	VXR3246	VXR3646	VXR4046	VXR4446	VXR5246	VXR6046	No Grille	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	72 3/32"	Unit W.
	60 5/16"	62 5/16"	64 5/16"	66 5/16"	68 5/16"	70 5/16"	72 3/32"	76 3/32"	80 3/32"	84 3/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	6'-8 19/32"	R.O. W.
	5'-0 13/16"	5'-2 13/16"	5'-4 13/16"	5'-6 13/16"	5'-8 13/16"	5'-10 13/16"	6'-0 19/32"	6'-4 19/32"	6'-8 19/32"	7'-0 19/32"	R.O.H.
24											Call Size
	VXR2050	VXR2450	VXR2850	VXR3250	VXR3650	VXR4050	VXR4450	VXR5250	VXR6050	No Grille	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	72 3/32"	Unit W.
	64 5/16"	66 5/16"	68 5/16"	70 5/16"	72 5/16"	74 5/16"	76 3/32"	80 3/32"	84 3/32"	88 3/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	6'-8 19/32"	R.O. W.
	5'-4 13/16"	5'-6 13/16"	5'-8 13/16"	5'-10 13/16"	6'-0 13/16"	6'-2 13/16"	6'-4 19/32"	6'-8 19/32"	7'-0 19/32"	7'-4 19/32"	R.O.H.
28											Call Size
	VXR2058	VXR2458	VXR2858	VXR3258	VXR3658	VXR4058	VXR4458	VXR5258	VXR6058	No Grille	Call Size
	23 3/8"	27 3/8"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	72 3/32"	Unit W.
	72 5/16"	74 5/16"	76 5/16"	78 5/16"	80 5/16"	82 5/16"	84 3/32"	88 3/32"	92 3/32"	96 3/32"	Unit H.
	2'-0"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	6'-8 19/32"	R.O. W.
	6'-0 13/16"	6'-2 13/16"	6'-4 13/16"	6'-6 13/16"	6'-8 13/16"	6'-10 13/16"	7'-0 19/32"	7'-4 19/32"	7'-8 19/32"	8'-0 19/32"	R.O.H.