



# SS20 Single Slider Sizes

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width for Call Widths < 44 = Call Width + 3 3/8". For Call Widths ≥ 44 = Call Width + 2 15/16". Specified in inches.
4. Unit / Frame Height = Call Height + 2-5/8". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 5/8". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 3/8". Specified in feet and inches.
7. Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
8. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
9. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
10. Unit may be mullered with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
11. The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call Height - SH/DH	Call Height - SS/FX	Unit/Frame Height	R.O. Height	28	32	36	40	44	52	60	68	Call Width
		22 5/8"	1'-11"	31 3/8"	35 3/8"	39 3/8"	43 3/8"	46 15/16"	54 15/16"	62 15/16"	70 15/16"	Unit/Frame Width
		26 5/8"	2'-3"	2'-8"	3'-0"	3'-4"	3'-8"	3'-11 1/2"	4'-7 1/2"	5'-3 1/2"	5'-11 1/2"	R.O. Width
20	20	22 5/8"	1'-11"	1	9	17	25	33	41	49	57	<b>Grille Patterns</b>  No Grille  Colonial  Lexington
24	24	26 5/8"	2'-3"	2	10	18	26	46	42	50	58	
14	30	32 5/8"	2'-9"	3	11	19	27	35	43	51	59	
16	34	36 5/8"	3'-1"	4	12	20	28	36	44	52	60	
20	42	44 5/8"	3'-9"	5	13	21	29	37	45	53	61	
22	46	48 5/8"	4'-1"	6	14	22	30	38	46	54	62	
24	50	52 5/8"	4'-5"	7	15	23	31	39	47	55	63	
28	58	60 5/8"	5'-1"	8	16	24	32	40	48	56	64	




# SS20 Slider Picture Window Sizes


- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted. Call Width identifies the size of the center fixed lite.
- Unit / Frame Width for Call Widths < 44 = (Call Width x 2) + 9 1/8". For Call Widths ≥ 44 = (Call Width x 2) + 8 1/4". Specified in inches.
- Unit / Frame Height = Call Height + 2-5/8". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 3/8". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 3/8". Specified in feet and inches.
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call Height - SH/DH	24	28	32	36	40	44	52	Call Width (center)
20	57 1/8"	65 1/8"	73 1/8"	81 1/8"	89 1/8"	96 1/4"	112 1/4"	Unit/Frame Width
24	4'-9 1/2"	5'-5 1/2"	6'-1 1/2"	6'-9 1/2"	7'-5 1/2"	8'-0 5/8"	9'-4 5/8"	R.O. Width
14	22 5/8"	22 5/8"	22 5/8"	22 5/8"	22 5/8"	22 5/8"	22 5/8"	1'-11"
16	26 5/8"	26 5/8"	26 5/8"	26 5/8"	26 5/8"	26 5/8"	26 5/8"	2'-3"
20	32 5/8"	32 5/8"	32 5/8"	32 5/8"	32 5/8"	32 5/8"	32 5/8"	2'-9"
22	36 5/8"	36 5/8"	36 5/8"	36 5/8"	36 5/8"	36 5/8"	36 5/8"	3'-1"
24	44 5/8"	44 5/8"	44 5/8"	44 5/8"	44 5/8"	44 5/8"	44 5/8"	3'-9"
28	48 5/8"	48 5/8"	48 5/8"	48 5/8"	48 5/8"	48 5/8"	48 5/8"	4'-1"
24	52 5/8"	52 5/8"	52 5/8"	52 5/8"	52 5/8"	52 5/8"	52 5/8"	4'-5"
28	60 5/8"	60 5/8"	60 5/8"	60 5/8"	60 5/8"	60 5/8"	60 5/8"	5'-1"


### Grille Patterns



No Grille



Colonial



Lexington

VPV2420	VPV2820	VPV3220	VPV3620	VPV4020	VPV4420	VPV5220
VPV2424	VPV2824	VPV3224	VPV3624	VPV4024	VPV4424	VPV5224
VPV2430	VPV2830	VPV3230	VPV3630	VPV4030	VPV4430	VPV5230
VPV2434	VPV2834	VPV3234	VPV3634	VPV4034	VPV4434	VPV5234
VPV2442	VPV2842	VPV3242	VPV3642	VPV4042	VPV4442	VPV5242
VPV2446	VPV2846	VPV3246	VPV3646	VPV4046	VPV4446	VPV5246
VPV2450	VPV2850	VPV3250	VPV3650	VPV4050	VPV4450	VPV5250
VPV2458	VPV2858	VPV3258	VPV3658	VPV4058	VPV4458	VPV5258



# SS20 Slider Equal Vent Window Sizes

- The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
- The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted. Call Width identifies the size of the center fixed lite.
- Unit / Frame Width = (Call Width x 2) + 9-1/8". Specified in inches.
- Unit / Frame Height = Call Height + 2-5/8". Specified in inches.
- Rough Opening Width = Unit/Frame Width + 3/8". Specified in feet and inches.
- Rough Opening Height = Unit/Frame Height + 3/8". Specified in feet and inches.
- Clear Opening or egress dimensions are available on the Dimensions page at the back of this section.
- A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
- All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
- Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
- The standard jamb depth is 1-5/8". Jamb Extension may be added to increase the jamb depth to 4-9/16" (typical wall thickness) or to 6-9/16". Specify which jamb depth needed.

Call Height - SH/DH	20	24	28	32	36	Call Width (center)	
20	16	20	24	28	32	36	Call Width (center)
22	16	20	24	28	32	36	Unit/Frame Width
24	16	20	24	28	32	36	R.O. Width
28	16	20	24	28	32	36	


  

Call Height - SH/DH	20	24	28	32	36	Call Width (center)	
20	16	20	24	28	32	36	Call Width (center)
22	16	20	24	28	32	36	Unit/Frame Width
24	16	20	24	28	32	36	R.O. Width
28	16	20	24	28	32	36	


### Grille Patterns



No Grille



Colonial



Lexington